

Full ball bearing with hole to load the ball



Part Number	Bore (in.)	Outside Diameter (in.)	Inner Ring Width (in.)	Outer Ring Width (in.)	Inner Land Diameter (in.)	Inner Ring Chamfer (in.)	Outer Ring Chamfer (in.)	Radial Limit Load Rating (lbs.)	Thrust Limit Load Rating(lbs.)
B538/B538DD	0.625	1.0625	0.281	0.25	0.777	0.015	0.015	3280	1500
B539/B539DD	0.75	1.1875	0.281	0.25	0.895	0.015	0.015	3750	1700
B540/B540DD	0.875	1.3125	0.281	0.25	1.016	0.015	0.015	4220	1900
B541/B541DD	1.0625	1.5	0.281	0.25	1.216	0.015	0.015	5000	2200
B542/B542DD	1.3125	1.75	0.281	0.25	1.451	0.015	0.015	5950	2700
B543/B543DD	1.5625	2	0.281	0.25	1.702	0.015	0.015	6880	3200
B544/B544DD	1.8125	2.25	0.281	0.25	1.97	0.015	0.015	7980	3600
B545/B545DD	2.0625	2.625	0.281	0.25	2.286	0.015	0.015	9220	4000
B546/B546DD	2.3125	2.875	0.281	0.25	2.527	0.015	0.015	10150	4400